

# CABLE DEREELER RAMA 1250

## AUTOMATIC FEEDING OF CABLES



### FEATURES

- Both dereelers are suitable for large drums and also stiff cables. As an option the cable reservoir / accumulator is available with one or two additional loops
- The unique cable-recoil-detection observes the feeding direction and immediately stops the machine in case of fixed cable ends (to the drums) or jammed cable on a drum.

### TECHNICAL DATA

Performance	rama 1250
Max. drum diameter	1250 mm
Min. drum diameter	410 mm (from the ground)
Max. drum width	950 mm
Min. drum width	240 mm
Cable spool diameter	up to 1260 mm
Cable spool width	up to 850 mm
Cable spool weight	up to 1000 kg
Max. cable outside diameter Version 18	18 mm
Version 35	35 mm
Max. Cable spool speed	145 min <sup>-1</sup>
Cable reservoir volume 1 additional loop (2 pulleys) 2 additional loops (4 pulleys)	With swinging arm reservoir
Spool clamping system	ramatech spool clamping system
Operation	Hand-held remote control
Interfaces	Communication interface to cable processing machines
Drive	Variable-frequency 3-phase AC motor with electro-mechanical brake
Electrical connection	3 x 400 VAC, N 32 A
Compressed air supply	6 bar
Weight	845 kg
Dimension (L x W x H)	1920 x 1580 x 1380 mm

LOCATION SWITZERLAND

**Ramatech Systems AG** . Hohenrainstrasse 36 . CH - 6280 Hochdorf  
Phone: +41 41 914 26 26 . E-Mail: [info@ramatech.ch](mailto:info@ramatech.ch)

© Ramatech systems 2021

LOCATION GERMANY

**Ramatech Systems GmbH** . Messerschmittstraße 30 . D - 89231 Neu-Ulm  
Phone: +49 731 40 199 200 . E-Mail: [info@ramatech.de](mailto:info@ramatech.de)