

MOBILE CABLE WINDER MRW 650

Cable winding on cable coils



FEATURES

- High degree of flexibility and winding power
- Mobile winder for winding cable rings
- Cables with diameters up to 45 mm can be rewound easily and quickly from reel rack systems or a reel stand
- Ergonomic working height for the removal of the finished cable coils
- Automatic laying for longer cable lengths is optionally available

The cable end from a reel rack system or reel stand is fed through the measuring and laying unit. The operator attaches the cable to the ring winding attachment, enters the target length on the touchscreen and starts the winding process. During the winding process, the speed can be selected variably. Shortly before reaching the target length, the unit brakes and stops. The safety door is opened, the cable is cut at the marking and the cable ring can be removed.

TECHNICAL DATA

| Performance | Winding coils |
|-------------------------------|---------------------------------------------------------------------------------------------|
| Inner diameter | 300 - 500 mm |
| Outer Diameter | 650 mm |
| Coil height | 200 mm |
| Flexible cable up to diameter | max. 45 mm |
| Weight cable coils | 50 kg |
| Speed | up to 3 m/s |
| Control system | PLC and LCD operating terminal. Programmable are: Inner and outer diameter. Laying gradient |
| Revolution | max. 192 min.-1 |
| Optional | Automatic laying |
| Special | Mobile winder for winding cable coils |

LOCATION SWITZERLAND

Ramatech Systems AG . Hohenrainstrasse 36 . CH - 6280 Hochdorf
Phone: +41 (0)41 914 26 26 . E-Mail: info@ramatech.ch

LOCATION GERMANY

Ramatech Systems GmbH. Messerschmittstraße 30 . D - 89231 Neu-Ulm
Phone: +49 731 40 199 200 . E-Mail: info@ramatech.de