



UWINDING STANDS

FOR EASY DEREELING (PASSIVE / ACTIVE) OF CABLE DRUMS



FEATURES

- Three versions for different cable drum sizes
- Drums up to max. 12 tonnes weight and 3.20 metres diameter possible
- In addition to passive unwinding, a motorised attachment for a rubber wheel drive is optional available
- Easy loading and unloading by hand or forklift crane
- Operation via remote control possible
- Columns anchored in the floor
- Drum shafts, cluffs and shaft locks available in different sizes

TECHNICAL DATA

Performance	AWB 1700	AWB 2000	AWB 3200
Max. Drum diameter	up to 1700 mm	up to 2000 mm	up to 3200 mm
Min. Drum diameter	from 400 mm	from 600 mm	from 800 mm
Max. Drum width	1100 mm	1200 mm	1600 mm
Min. Drum width	350 mm	500 mm	500 mm
Max. Drum weight	3,5 t	5 t	12 t
Coil drilling	customized but max. 90 mm diameter	customized but max. 120 mm diameter	customized but max. 120 mm diameter
Dereeling speed	up to 2 m/s	up to 2 m/s	up to 2 m/s
Dimension (L x B x H) (with drum shaft and motor)	approx. 1700 x 1800 x 1400 mm (approx. 1700 x 2500 x 2400 mm)	approx. 1880 x 1900 x 2700 mm (approx. 1880 x 2600 x 1200 mm)	approx. 2600 x 2600 x 2400 mm (approx. 2600 x 3000 x 3700 mm)
Machine weight without drive	approx. 300 kg	approx. 300 kg	approx. 850 kg
Machine weight with motor attachment	approx. 850 kg	approx. 950 kg	approx. 1.000 kg

LOCATION SWITZERLAND

Ramatech Systems AG . Hohenrainstrasse 36 . CH - 6280 Hochdorf
Phone: +41 (0)41 914 26 26 . E-Mail: info@ramatech.ch

© Ramatech systems 2023

LOCATION GERMANY

Ramatech Systems GmbH. Messerschmittstraße 30 . D - 89231 Neu-Ulm
Phone: +49 731 40 199 200 . E-Mail: info@ramatech.de