



VARIO WINDER VW 400 and VW 700

FOR A QUICK CHANGE BETWEEN DRUM AND RING



FEATURES

- Variable winding possible on small reels and in ring form for thin cables
- Change between reel and ring in seconds
- Flush and tidy laying pattern thanks to cable accumulator and automatically traversing laying unit
- High winding speeds achievable
- Cables up to 20 mm diameter can be processed
- Ergonomic working height for loading and unloading
- Easy tying of rings thanks to groove for quick insertion of cable ties
- Convenient clamping of cable drums with foot pedal

TECHNICAL DATA

Performance	VW 400	VW 700
Cable ring inner diameter	150 mm	150 mm
Max. cable ring outer diameter	400 mm	400 mm
Cable ring height	200 mm	200 mm
Min. drum diameter	150 mm	150 mm
Max. Drum diameter	400 mm	720 mm
Drum width	350 mm	610 mm
Cable diameter	1 - 20 mm	1 - 20 mm
Weight of cable rings/reel	up to 40 kg	up to 80 kg
Winding speed	up to 3 m/s	up to 3 m/s
Power Supply	3 x 400 VAC / 32 A	3 x 400 VAC / 20 A
Weight	570 kg	650 kg
Dimension (L x B x H)	2177 x 1548 x 1900 mm	2457 x 1870 x 1900 mm
Equipment	Pneumatic cutting unit Length measurement Cable clamping Cable feed	Pneumatic cutting unit Length measurement Cable clamping Cable feed

LOCATION SWITZERLAND

Ramatech Systems AG . Hohenrainstrasse 36 . CH - 6280 Hochdorf
Phone: +41 (0)41 914 26 26 . E-Mail: info@ramatech.ch

© Ramatech systems 2024

LOCATION GERMANY

Ramatech Systems GmbH. Messerschmittstraße 30 . D - 89231 Neu-Ulm
Phone: +49 731 40 199 200 . E-Mail: info@ramatech.de